



Type 2

Bee Meter VPOS Touch

A seamless solution for charging EVs in commercial properties including shopping centers, commercial real estate, hotels, workplaces, parking lots, cities, and municipalities.

The Bee Meter VPOS Touch is the first universal charger with an open payment system. Our smart, secure, and feature-rich solution enables businesses to take initiative while maximizing revenue and modernizing properties.



Real-Time Reporting

Receive notifications and oversee assets in one place



Multi-Language

Operates in 15 languages with unique voice interaction features



e-Receipt

Send your customers receipts over SMS or email



24/7 Monitoring

Real-time support, remote updates and repairs



Safe & Durable

Tested to the highest degree of electrical safety



Park & Charge

Switch to parking mode and increase revenue



Open Payment System

Accept any type of payment method



Dynamic Load Management

Optimize device up-time and avoid overloading the grid



Electrical Data	AC Power Supply AC Input Voltage Maximum Input / Output Current Maximum Input / Output Power Number of Plugs AC Output Voltage	3P + N + PE 230-400 VAC +/-10, 32Amax 22kW one 230-400 VAC +/-10 (3P + N + PE)
Communication	Interface Protocol Wireless Connection	OCPP 1.6 Supported Bluetooth, Wi-Fi, GSM/GPRS
Supported Payment Schemes	Debit & Credit Cards Mobile & NFC Payments Prepared cards & closed environments Static and Dynamic QR codes	Swipe, contact, contactless, EMV chip cards Google Pay, Apple Pay, MobilePay Bluecode, Swish and more Alipay, WeChat Pay and others
Safety & Protections	Safety Protections Power Limit Control Type 1 Socket Protection Dynamic Load Management Available Connections	Electronic RCD 30mA Type A Electronic 6mA DC Fault current detection Mode 3 PWM control according to ISO/IEC 61851-1 IEC-62196 Type 2 connector Yes J-1772 Type 1 Connector 16.4" cable
Enclosure & Environmental Conditions	IP Rating Charger Impact Protection Payment Terminal Impact Protection Enclosure Material Operating Temperature Ambient Temperature Storage Status LEDs Light Beacon Built-in Energy Meter	IP55 IK10 IK8 PC + UV (-25°C) to (+55°C) (-30°C) to (+70°C) Yes RGB color indicator Yes, MID optional
Weight & Dimensions (WxHxD)	Cable Socket	450x300x180 mm, 8Kg 480x300x180 mm, 6Kg
Warranty	5 year limited warranty	
Standards & Certifications	ROHS REACH CE Compliant	
Optional Devices	Type 2 Socket Protection Dynamic Load Management Pedestal Extended Cable	Shutter Yes Yes 8m